

MOT98 MOT98-A MOT-IC-F

motors



MOT98 for: TP6, TP6/PR-B, TP6/S, TP6/V, TP6/R, TP6/97, TP6/PR-B/97
(Cod.7915031=110V / 7915030=220V)



MOT-IC-F for TP/IC-F MACHINE
foot control pedal included
(Cod.64.OL01=110V / 64.OL02=220V)



MOT98/A for: TP6/PR-F and TP6/V- PR
(Cod.7915033 =110V / 7915032 =220V)

SPECIFICATIONS OF MOTOR MOT98- MOT 98/A

ELECT.SUPPLY = 220 or 110V - 50 Hz - 100VA
LENGTH = MOT98 42 cm and MOT98/A 51 cm
WIDTH = MOT98 and MOT98/A 29 cm
HEIGHT = MOT98 and MOT98/A 16 cm
PACKING = 59x59x35 cm
VOLUME = 0,121 m³
MOTOR WEIGHT = MOT98 9 kg - MOT98/A 10 kg
GROSS WEIGHT = MOT98 11 kg - MOT98/A 12 kg

SPECIFICATIONS OF MOTOR MOT-IC-F

ELECT.SUPPLY = 220 or 110V - 50 Hz - 50 VA
LENGTH = 48 cm
WIDTH = 17 cm
HEIGHT = 20 cm
PACKING = 41x53x26 cm
VOLUME = 0,056 m³
MOTOR WEIGHT = 6 kg
GROSS WEIGHT = 9 kg

OPTIONAL FOOT PEDAL CONTROL FOR MOT98 AND MOT98/A (Cod. 600023)

The OLAMEF MOT98 and MOT-IC-F are motor drive units that attach to the TP6 manually operated machines.

They are considered accessories that can be purchased separately or as part of the equipment when any model is supplied in the motorized version. The 3 motors come with a speed control knob to enable to adjust the operation speed. The emergency button immediately stops the electric supply. The operation is also stopped when the safety cover is removed. The power control relay ensures the motor starting only when the operator uses the ON/OFF switch.

WARNING:The motor drive unit is always recommended when using the loose component feeders: CS10 - CS20 - CS30 or CS40.