



Rundsteckhülsen und Rundstecker

Prises et fiches de contact rondes

Round plug and bullet connectors

Werkstoff:

BZ = Bronze
 MS = Messing

Strombelastbarkeit:

0.5 - 1.0 mm² / 10 A max.
1.5 - 2.5 mm² / 15 A max.
4.0 - 6.0 mm² / 25 A max.

Oberflächenbehandlung: Code

bl = blank (0)
 ag = versilbert (1)
 au = vergoldet (2)
 sn = reinverzinkt (7)

Bestellbeispiel
Exemple de commande:
Example of order:

3881.60
 (3881 MS bl)

Matière:

BZ = bronze
 MS = laiton

Intensité admissible:

0.5 - 1.0 mm² / 10 A max.
1.5 - 2.5 mm² / 15 A max.
4.0 - 6.0 mm² / 25 A max.

Traitements de surface: Code

bl = brut (0)
 ag = argenté (1)
 au = doré (2)
 sn = étamage pur (7)

Material:



BZ = bronze
 MS = brass

Current carrying capacity:

0.5 - 1.0 mm² / 10 A max.
1.5 - 2.5 mm² / 15 A max.
4.0 - 6.0 mm² / 25 A max.

Surface-plating: Code

bl = clean (0)
 ag = silver-plated (1)
 au = gold-plated (2)
 sn = pure tin-plated (7)



mm ² (AWG)	für Stecker pour fiche for plug	Artikel-Nr. Numéro d'article Part-No.	L1 mm	L2 mm	A1 mm	A2 mm	S mm	Stand.- Packg	Werkzeuge Outils Tools
0.25-0.5 (24-22)	ø 2.4 mm	3881.6() MS	18	6.5	9.5	4.5	0.32	1000	3975C
	ø 2.8 mm	3882.6() MS	18	6.5	9.5	4.5	0.32	1000	
0.5-1 (22-18)	ø 1.5 mm	3883.6() MS	17	7	6.1	3	0.3	1000	3975B 3984A / 3997 3987D
	ø 2.4 mm	3886.6() MS	16	8.5	5.5	2.5	0.25	1000	
	ø 2.4 mm	3887.6() MS	14.3	6.5	6.1	3	0.32	1000	
	ø 4.0 mm	3888.2() BZ	20	9	9	3.5	0.35	500	
	ø 5.0 mm	3889.2() BZ	20	9	9	3.5	0.45	500	
1.5-2.5 (16-14)	ø 4.0 mm	3891.2() BZ	20	9	9	4.5	0.35	500	3975C 3976 3984A / 3997 3988
2.5 (14)	ø 3.0 mm	3885.2() BZ	18	7	9	4.5	0.35	1000	
4-6 (12-10)	ø 5.0 mm	3894.2() BZ	20	9	9	4.5	0.45	500	