



Rundsteckhülsen und Rundstecker

Prises et fiches de contact rondes

Round plug and bullet connectors

Werkstoff:

BZ = Bronze
MS = Messing

Strombelastbarkeit:

0.5 - 1.0 mm² / 10 A max.
1.5 - 2.5 mm² / 15 A max.
4.0 - 6.0 mm² / 25 A max.

Oberflächenbehandlung: Code

bl = blank (0)
ag = versilbert (1)
au = vergoldet (2)
sn = reinverzinkt (7)

Bestellbeispiel

Exemple de commande:

Example of order:

3881.60

(3881 MS bl)

Matière:

BZ = bronze
MS = laiton

Intensité admissible:

0.5 - 1.0 mm² / 10 A max.
1.5 - 2.5 mm² / 15 A max.
4.0 - 6.0 mm² / 25 A max.

Traitements de surface: Code

bl = brut (0)
ag = argenté (1)
au = doré (2)
sn = étamage pur (7)

Material:

BZ = bronze
MS = brass

Current carrying capacity:

0.5 - 1.0 mm² / 10 A max.
1.5 - 2.5 mm² / 15 A max.
4.0 - 6.0 mm² / 25 A max.

Surface-plating: Code

bl = clean (0)
ag = silver-plated (1)
au = gold-plated (2)
sn = pure tin-plated (7)

mm ² (AWG)	für Stecker pour fiche for plug	Artikel-Nr. Numéro d'article Part-No.	L1 mm	L2 mm	A1 mm	A2 mm	S mm	Stand- Packg	Werkzeuge Outils Tools
0.5-1 (22-18)	ø 4.0 mm	3896B.6() MS	20	9	9	4.5	0.4	500	3975C 3976 3984A / 3997 3988
1.5-2.5 (16-14)	ø 4.0 mm ø 5.0 mm	3897A.6() MS 3897B.6() MS	20 20	9 9	9 9	4.5 4.5	0.4 0.4	500 500	

