



Flachsteckhülsen mit Isolation

Clips femelles plats avec isolation

Flat receptacles with insulation

Werkstoff:
MS sn = Messing verzinkt
Temperaturbeständigkeit:
PVC -10°C bis +75°C

Strombelastbarkeit:
0.5 - 1.0 mm² / 10 A max.
1.5 - 2.5 mm² / 15 A max.
4.0 - 6.0 mm² / 25 A max.


Matière:
MS sn = laiton étamé
Résistant à une température de:
PVC -10°C à +75°C

Intensité admissible:
0.5 - 1.0 mm² / 10 A max.
1.5 - 2.5 mm² / 15 A max.
4.0 - 6.0 mm² / 25 A max.

Material:
MS sn = tin-plated brass
Temperature range:
PVC -10°C up to +75°C

Current carrying capacity:
0.5 - 1.0 mm² / 10 A max.
1.5 - 2.5 mm² / 15 A max.
4.0 - 6.0 mm² / 25 A max.

Bestellbeispiel:
Exemple de commande:
Example of order:
3908






Form A
mit Stützhülse
avec douille-support
with extra support-sleeve



Form B
ohne Stützhülse
sans douille-support
without extra support-sleeve

**9,5
mm**



Werkstoff Isolation Isolation en Insulation	mm ² (AWG)	für Steckungen pour languettes for tabs	Artikel-Nr. / Numéro d'article / Part-No.		L mm	A mm	øD mm	Stand- Packg	Werkzeuge Outils Tools	
			Farben Couleurs Colours	Form A						Form B
PVC	1.5-2.5 (16-14)	9.5 x 1.2		3919	3919S	26	10.5	2.3	200	3978 / 3982 3982A / 3984C 3984D 3984O / 3997 3986 / 3986A 3986B
	4-6 (12-10)	9.5 x 1.2		3914	3914S	28.5	13	3.4	200	