



Flachsteckhülsen

DIN 46247 Teil 1
 DIN 46340 Teil 1 zum Einrasten
 in Tüllen

Clips femelles plats

DIN 46247 partie 1
 DIN 46340 partie 1 pour encliqueter
 dans des boîtiers

Flat receptacles

DIN 46247 part 1
 DIN 46340 part 1 to engage
 in housings

Werkstoff:

BZ = Bronze
 MS = Messing

Matière:

BZ = bronze
 MS = laiton

Material:

BZ = bronze
 MS = brass

Strombelastbarkeit:

0.3 - 0.6 mm² / 2.5 A max.
0.75- 1.0 mm² / 6.0 A max.

Intensité admissible:

0.3 - 0.6 mm² / 2.5 A max.
0.75- 1.0 mm² / 6.0 A max.

Current carrying capacity:

0.3 - 0.6 mm² / 2.5 A max.
0.75- 1.0 mm² / 6.0 A max.

Oberflächenbehandlung: Code

bl = blank (0)
 ag = versilbert (1)
 au = vergoldet (2)
 ni = vernickelt (5)
 sn = reinverzinkt (7)

Traitements de surface: Code

bl = brut (0)
 ag = argenté (1)
 au = doré (2)
 ni = nickelé (5)
 sn = étamage pur (7)


Surface-plating: Code

bl = clean (0)
 ag = silver-plated (1)
 au = gold-plated (2)
 ni = nickel plated (5)
 sn = pure tin-plated (7)

Bestellbeispiel
Exemple de commande:
Example of order:

3760A.67
 (3760A MS sn)

2,8 mm



mm ² (AWG)	für Steckungen pour languettes for tabs	Artikel-Nr. Numéro d'article Part-No.	L1 mm	L2 mm	L3 mm	A1 mm	A2 mm	S mm	Stand- Packg	Werkzeuge Outils Tools
0.14-0.3 (26-22)	2.8 x 0.5	3760A.6() MS	14	6.3	-	5	2	0.25	2000	3975A 3984G / 3997 3987 3987D
	2.8 x 0.8	3762A.6() MS	14	6.3	-	5	2	0.25	2000	
	2.8 x 1.2	3762C.6() MS	14	6.3	-	5	2	0.25	2000	
0.3-0.6 (22-20)	2.8 x 0.5	3760B.6() MS	14	6.3	-	5.5	2.9	0.25	2000	3975B 3984G / 3997 3987 3987D
	2.8 x 0.8	3762B.6() MS	14	6.3	-	5.5	2.9	0.25	2000	
0.75-1 (20-18)	2.8 x 0.5	3764.6() MS	12.5	5	-	5.5	2.5	0.3	2000	3975B 3984A / 3997 3988
	2.8 x 0.5	3766.6() MS	14	6.3	-	5.5	2.5	0.25	2000	
	2.8 x 0.5	3768.6() MS	15.5	8	-	5.5	2.5	0.3	2000	
	2.8 x 0.8	3765.6() MS	12.5	5	-	5.5	2.5	0.3	2000	
	2.8 x 0.8	3767.2() BZ	14	6.3	-	5.5	2.5	0.25	2000	
	2.8 x 0.8	3767.6() MS	14	6.3	-	5.5	2.5	0.25	2000	
0.14-0.3 (26-22)	2.8 x 0.8	3763A.6() MS	14	6.3	5.6	5	2	0.25	2000	3975A 3984G / 3997 3987 3987D
			15.5	8	8.3	5.5	2.5	0.3	2000	
0.75-1 (20-18)	2.8 x 0.8	3769.6() MS	15.5	8	8.3	5.5	2.5	0.3	2000	3975B 3984A / 3997 3988
			15.5	8	8.3	5.5	2.5	0.3	2000	
0.75 (20)	2.8 x 0.8	3761.6() MS	9	5	-	2	-	0.25	2000	3975B 3987D
0.5-1 (22-18)	2.8 x 0.5	3764W.6() MS	7.8	5	-	7.2	2.5	0.3	1000	3973 3976 3987 3988
			7.8	5	-	7.2	2.5	0.3	1000	








Vogt Verbindungstechnik

**2,8
mm**

--	--	--	--	--	--	--	--	--	--	--

für Steckungen
pour languettes
for tabs



Artikel-Nr.
Numéro d'article
Part-No.

→ 3762E.6() MS

3762F.6() MS

379908.6() MS

3758.6() MS

3766W.6() MS

Stand.-Packg.
1000

2.8x0.8
1000

0.5-1.0 mm²
2.8x0.8
1000

0.3-0.6 mm²
2.0x0.3
2000

0.5-1 mm²
2.8x0.5
2000

Werkzeuge
Outils / Tools

3975B

3975B / 3987DN

3975B / 3988N