



- Hardwearing homogeneous contract sheet and tile floorcovering
- Static dissipative properties
- Engineered for ESD protection


SPECIFICATION



2.0mm
0.080in



2m x 20m = 40m²
6ft 6in x 65ft = 47sq yds



608 x 608mm = 5.17m²
23.9in x 23.9in = 6.2sq yds



3400g/m²
6.3lbs/sq yd



GENERAL PERFORMANCE

EN 649
ASTM F1913
ASTM F1700
AS2055.1




Agrément – G5ws



REACTION TO FIRE

EN 13501-1 Class Bfl-S1
EN ISO 9239-1 8kw/m²
EN ISO 11925-2 pass
ASTM E648 Class 1
ASTM E662 <450



ELECTRICAL PROPERTIES

EN 1081 R ₁ /R ₂ <10 ⁹ ohms	EN 1815 <2kv
ESD S 7.1 1 x 10 ⁶ - 1 x 10 ⁹ ohms	AATCC 134 <2kv
IEC 61340-4-1 1995 DIF Class 3 R _G	IBM Conforms
IEC 61340-4-1 2003 R _G 1 x 10 ⁶ - 1 x 10 ⁹ ohms	Federal Test 101C 1.4 secs Avg

All SD products require minimum 40% RH



SLIP RESISTANCE
EN 13893 Class DS



ABRASION
EN 649 Group M




RESIDUAL INDENTATION

ASTM F970 (modified)
static load 750 psi



APPLICATIONS

Polyflor Static Dissipative products are engineered for use where static control is required. These floorcoverings are ideal for use in telecommunications installations, computer rooms and healthcare facilities such as scanner rooms, X-ray suites and operating theatres.



For information regarding handling and installation, advice on specific applications, adhesives, maintenance and chemical resistance, consult Polyflor.
Access Panel applications require specific fitting instructions, to ensure product performance and achievement of electrical results outlined.
Contact Polyflor Customer Technical Support Department on 0161 767 1111 for information.

POLYFLOR
ESD

POLYFLOR SD

PERFORMANCE AND
PROPERTIES



POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
TEL: +44 (0)161 767 1111 UK SALES DIRECT: +44 (0)161 767 1122 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM WWW.POLYFLOR.COM
UK SAMPLE REQUESTS: +44 (0)161 767 2551

James Halstead
FLOORING