



Vogt Verbindungstechnik

Flachsteckhülsen

DIN 46247 Teil 4

Clips femelles plats

DIN 46247 partie 4

Flat receptacles

DIN 46247 part 4

Werkstoff:

BZ = Bronze
 MS = Messing

Matière:

BZ = bronze
 MS = laiton

Material:

BZ = bronze
 MS = brass

Strombelastbarkeit:

0.5 - 1.0 mm² / 10 A max.
1.5 - 2.5 mm² / 15 A max.
4.0 - 6.0 mm² / 25 A max.

Intensité admissible:

0.5 - 1.0 mm² / 10 A max.
1.5 - 2.5 mm² / 15 A max.
4.0 - 6.0 mm² / 25 A max.

Current carrying capacity:

0.5 - 1.0 mm² / 10 A max.
1.5 - 2.5 mm² / 15 A max.
4.0 - 6.0 mm² / 25 A max.

Oberflächenbehandlung: Code

bl = blank (0)
 ag = versilbert (1)
 au = vergoldet (2)
 ni = vernickelt (5)
 sn = reinverzinkt (7)

Traitements de surface: Code

bl = brut (0)
 ag = argenté (1)
 au = doré (2)
 ni = nickelé (5)
 sn = étamage pur (7)

Surface-plating: Code

bl = clean (0)
 ag = silver-plated (1)
 au = gold-plated (2)
 ni = nickel plated (5)
 sn = pure tin-plated (7)

Bestellbeispiel


Exemple de commande:

Example of order:

3835T.60


(3835T MS bl)

9,5 mm



mm ² (AWG)	für Steckungen pour languettes for tabs	Artikel-Nr. Numéro d'article Part-No.	L1 mm	L2 mm	L3 mm	A1 mm	A2 mm	S mm	Stand- Packg	Werkzeuge Outils Tools
4-6 (12-10)	9.5 x 1.2	3835T.6() MS	25.2	11.5	-	9	4.4	0.45	200	
6 (6+2.5) (10) (10+14)	9.5 x 1.2	3835V.6() MS	24.5	12	-	8.5	4	0.6	200	3975C 3988

für Steckungen
pour languettes
for tabs



Artikel-Nr.
Numéro d'article
Part-No. → **3835U.6() MS**

Stand.-Packg. 9.5x1.2
1000